6.897
L6.01
~~L6.046~~, 2003
Mar. 3

What if OPT can change the list too?

- static optimality is "cheating": algorithm can change list dynamically but comparing to OPT that can't! (in stochastic model, this didn't matter)

- dynamic optimality / c-competitive:

  ∀ request sequence: cost(algorithm) ≤ c · cost(best algorithm for that request seq.)

  i.e. cost((online) algorithm) ≤ c · cost((offline) OPT)

  (online algorithm: only learns request sequence as the searches happen)

  (offline OPT: knows request sequence ahead of time → omniscient)

- Sleator & Tarjan cost model:
  - pay i to find element in position i
  - free to move found element anywhere closer to front
  - pay 1 per swap of 2 adjacent elements

    ↳ a bit pricey... though no algs. so far do any such swaps

---

- FC is not $O(1)$-competitive
- * MTF is 2-competitive

} [Sleator & Tarjan – CACM 1985]

- No deterministic algorithm is < 2-competitive [Karp & Raghavan]

- Bit algorithm:
  - initially assign random bit to each element
  - upon access, flip the bit, & if 1, MTF.
- Bit is 1.75-competitive against oblivious adversary

[Reingold, Westbrook, Sleator – Algorithmica 1994]

- Best alg. so far is 1.6-competitive [Albers, von Stengel, Werchner – IPL 1995]
- No alg. is < 1.5-competitive [Teia – IPL 1993]

OPEN: close randomized gap between 1.5 & 1.6

See also Chapter 2 of [Borodin, El-Yaniv – C.U.P. 1998] for related open problems